

# AXISTECH CAMERA SOLUTIONS SPEC SHEET

## Specifications

Model	AXCAM-1B8-P240-0-S4G	AXCAM-1B8-S120-105-S4G	AXCAM-2B8-S150-135-S4G	AXCAM-1D2PTZ-S240-135-S4G
Configuration	240v Static Camera Unit	Solar Static Camera Unit	Solar Static Dual Camera Unit	Solar PTZ Camera Unit
Camera	Single 8.0MP static	Single 8.0MP static	2x 8.0MP static	Single Dome PTZ 2.0MP 4.8 ~ 120mm Motorised Lens 25x Optical Zoom Pan: 0 ~ 360° (endless) Tilt: -15 ~ 90° / Auto-flip 180°
Power	12V / 240v powered	120W Solar	150W Solar	240W Solar (2x120W)
Battery backup	Nil (UPS 2-5hr optional)	135AH (>2 days)	135AH (>2 days)	135AH (>2 days)
Connectivity	3G/4G/LTE Single SIM modem	3G/4G/LTE Single SIM modem	3G/4G/LTE Single SIM modem	3G/4G/LTE Single SIM modem
Onboard storage	256GB (approx. 60days)	256GB (approx. 60days)	256GB (approx. 60days)	256GB (approx. 60days)
Housing	Pre-assembled in IP66 ABS plastic enclosure	Pre-assembled in IP66 powder coated steel enclosure	Pre-assembled in IP66 powder coated steel enclosure	Pre-assembled in IP66 powder coated steel enclosure
Installation	Units supplied with mounts, bolts and u-bolts required for pole or shed installation. For pole install recommended 100x100x3mm square galvanized tube. Poles and installation can be provided if required.			
Additional upgrades	<ul style="list-style-type: none"> <li>Motion triggered flood LED lighting</li> <li>Motion triggered pre-recorded notification/warning</li> <li>Motion triggered combined flood LED lighting and pre-recorded notification/warning</li> <li>Dual SIM modem and high gain antennae</li> <li>Thermal imaging camera</li> <li>Optional upgrade to lighter weight lithium batteries</li> <li>Providing modems that also offer Wi-Fi capabilities</li> </ul>			

Customisations are also available. For more information, please visit [axistech.co](http://axistech.co) or send us an email at [info@axistech.co](mailto:info@axistech.co)